

## D-TEC Mineral Diesel Engine Oil SAE 70 CF

### Product Description

**D-TEC SAE 70 CF** is a high-performance, heavy-duty diesel engine oil formulated for optimal protection and performance in older turbocharged and non-turbocharged diesel engines operating under normal conditions. It meets the API CF/SF specifications, ensuring compatibility with a wide range of engines from major manufacturers.

### Performance Benefits

- **Maximum Cleanliness:** Maintains cleaner engines for reduced wear and improved performance.
- **Reduced Engine Maintenance Costs:** Extends oil drain intervals and minimizes maintenance needs.
- **Superior Thermo-Oxidative Stability:** Resists thickening and breakdown at high temperatures, ensuring extended oil life.
- **Excellent Anti-Wear Technology:** Protects critical engine components from wear and tear for longer service life.

### Health, Safety, and Environment

- Avoid prolonged or repeated contact with used oil.
- Wear protective gloves and wash hands thoroughly with soap and water after handling.
- Do not dispose of used oil in drains or the environment. Take it to an authorized used oil collection point

### Typical Properties

Property	Method	Units	Value
Viscosity Grade	-	-	70
Density @ 15°C	ASTM D1298	kg/L	0.8995
Viscosity @ 100°C	ASTM D445	cSt	27.85
Viscosity @ 40°C	ASTM D445	cSt	413.9
Viscosity Index	ASTM D2270	-	93
Pour Point	ASTM D97	°C	-15
Flash Point	ASTM D92	°C	280
Total Base Number (TBN)	ASTM D2896	mg KOH/g	10.50

### Application

- Ideal for older trucks and buses
- Cost-effective lubrication solution for off-highway applications like agricultural tractors
- Recommended for use in engines from Caterpillar, Cummins, Detroit Diesel, Mack, Volvo, Scania, Renault, Iveco, and many other diesel engine manufacturers.

### Meets and Exceeds

- Meets and exceeds : API CF/SF

### Storage Instructions

- Store in a cool, dry place away from sunlight, freezing temperatures, and extreme heat (not exceeding 60°C).
- Drums should be stored horizontally to prevent contamination and preserve labeling.

