

## DEXÖ Automatic Transmission Fluid Type A Suffix A

### Product Description

**DEXÖ ATF Type A Suffix A** is a high-quality mineral-based automatic transmission fluid designed to meet the lubrication requirements of older generation automatic transmissions, power steering systems, hydraulic systems, and torque converters. It ensures durability and reliable performance for heavy-duty vehicles, off-road construction equipment, agricultural machinery, and older passenger cars.

### Performance Benefits

- **Oxidation and Thermal Stability:** Prolongs fluid life by resisting breakdown under high temperatures.
- **Friction Retention:** Ensures smooth and consistent shifting performance.
- **Shear Stability:** Maintains fluid viscosity under heavy load conditions.
- **Anti-Wear Properties:** Protects critical transmission components from wear and tear.
- **Corrosion Protection:** Guards against rust and corrosion in hydraulic and transmission systems.

### Health & Safety, Environment

- **Health and Safety:** This product is unlikely to present any significant health hazard when used as recommended. Avoid skin contact. Use protective gloves and wash exposed areas with soap and water.
- **Environmental Protection:** Dispose of used oil at authorized collection points. Do not discharge into drains, soil, or water.
- **Material Safety Data Sheet (MSDS):** Available upon request.

### Typical Properties

Property	Test Method	Value
Kinematic Viscosity @ 40°C	ISO 3104	43.45 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ISO 3104	7.985 mm <sup>2</sup> /s
Viscosity Index	ISO 2909	158
Density @ 15°C	ISO 12185	0.8511 g/cm <sup>3</sup>
Flash Point (COC)	ISO 2592	222°C
Pour Point	ISO 3016	-45°C

### Application

#### Recommended for use in:

- Automatic transmissions and power steering systems in heavy-duty vehicles and older passenger cars.
- Hydraulic systems in agricultural equipment and off-highway construction machinery.
- Powershift and industrial torque converters requiring GM Type "A" Suffix "A" level performance.

### Industry Specifications

Meets General Motors (GM) Type "A" Suffix "A" requirements.

### Additional Information

DEXÖ ATF Type A Suffix A is engineered for robust performance across a range of applications requiring GM Type "A" Suffix "A" fluid. For further advice or support, please consult your DEXÖ representative.

