

DEXÖ Automatic Transmission Fluid Dexron VI

Product Description

DEXÖ ATF Dexron VI is a 100% synthetic, low-viscosity, high-performance automatic transmission fluid engineered for modern automatic transmissions. Featuring advanced synthetic technology and powerful additives, it ensures exceptional aging and oxidation stability, smooth shifting under all conditions, and extended oil change intervals.

Performance Benefits

- **Outstanding Friction Characteristics:** Enhances gear shifting performance and minimizes vibrations.
- **High Oxidation and Thermal Stability:** Prolongs transmission fluid life and prevents sludge/deposit formation.
- **Excellent Low-Temperature Performance:** Ensures reliable operation in extreme cold conditions.
- **Superior Wear Protection:** Extends the life of the transmission system.
- **Fuel Economy Benefits:** Reduces friction for better efficiency.
- **Anti-Foam and Corrosion Protection:** Maintains fluid integrity and safeguards system components.
- **Wide Compatibility:** Suitable for automatic gearboxes, power steering systems, and transfer cases.

Health & Safety, Environment

- Refer to the Material Safety Data Sheet (MSDS) for comprehensive health and safety information.
- Ensure proper handling and disposal practices as per local regulations.

Typical Properties

Property	Test Method	Value
Density @ 15°C	ASTM D 4052	0.8355 g/cm ³
Viscosity @ 40°C	ASTM D445	30.12 mm ² /s
Viscosity @ 100°C	ASTM D445	6.125 mm ² /s
Viscosity Index	ASTM D2270	157
Brookfield Viscosity @ -40°C	ASTM D2983	9800 mPa.s
Pour Point	ASTM D97	-51 °C
Flash Point	ASTM D92	222 °C
Color	Visual	Red

Application

Recommended for use in:

- Automatic transmissions with or without slip lockup clutches.
- Transfer cases and power steering systems.
- Compatible with a broad range of American, Asian, and European vehicle manufacturers, including GM, Ford, Honda, Toyota, Hyundai, Mercedes-Benz, and others.
- Suitable for older transmissions requiring DEXRON III H or DEXRON II D fluids.

Meets and Exceeds

DEXO ATF DEXRON VI meets or exceeds the following specifications:

- **General Motors:** DEXRON VI
- **Ford:** MERCON LV, MERCON ULV
- **BMW:** M-1375.4, 83 22 0 142 516
- **Toyota:** WS
- **Mercedes-Benz:** MB 236.12, MB 236.14
- **Hyundai:** SP-IV, SP-IV-RR
- **Nissan:** Matic S, Matic P
- And many more (refer to full specifications).

Usage Recommendations

- Always follow the vehicle manufacturer's specifications and guidelines.
- Shake well before use.
- Use unmixed for optimal performance.
- Change intervals: every 150,000 Km or As recommended by the manufacturer or adapted to individual usage.

