

DEXÖ Continuously Variable Transmission SB-II

Product Description

DEXÖ CVT SB-II is a high-performance Technosynthese transmission fluid designed specifically for Subaru Lineartronic CVT gearboxes (2015 models onward). This premium fluid provides exceptional power transfer, smooth driving performance, and superior fuel efficiency while ensuring long-lasting durability and optimal protection.

Performance Benefits

- **Anti-Shudder Performance:** Ensures smooth, seamless shifting and enhanced driving comfort.
- **Fuel Efficiency:** Optimized to maximize torque and horsepower output for better mileage.
- **Thermal and Oxidation Stability:** Extends fluid life under extreme operating conditions.
- **Wear Protection:** Prevents wear on belts, chains, and pulleys, ensuring long-lasting transmission health.
- **Low-Temperature Performance:** Excellent flow properties for reliable cold-weather operation.
- **Seal Compatibility:** Protects seals from shrinkage, hardening, or cracking to prevent leaks.

Health and Safety

Before use, refer to the Safety Data Sheet (SDS) for complete health and safety information.

Typical Properties

Property	Test Method	Units	Value
Color	Visual	-	Green
Density @ 15°C	ASTM D4052	g/cm ³	0.8345
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	34.09
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	7.258
Viscosity Index	ASTM D2270	-	185
Brook Field Viscosity @ -40°C	ASTM D2983	mPa.s	7890
Flash Point	ASTM D92	°C	218
Foam, Seq I @ 24°C	ASTM D892	ml-ml	0-0
Foam, Seq II @ 93.5°C	ASTM D892	ml-ml	0-0
Foam, Seq III @ 24°C	ASTM D892	ml-ml	0-0

Application

- Designed for Subaru Lineartronic CVT systems, equivalent to Subaru CVT Fluid Lineartronic No. 2 (K0425Y0711).
- Not recommended for hybrid CVT units or automatic transmissions other than CVTs.

Usage Guidelines

Can be mixed only with similar CVT fluids. Change interval: Follow the vehicle manufacturer's recommendations.

Always consult the owner's manual for compatibility and specific fluid requirements.

