

DEXÖ CVT TC

Product Description

DEXÖ CVT TC is a high-quality synthetic transmission fluid, specially formulated for belt-driven continuously variable transmissions (CVTs) in passenger cars. Engineered to deliver superior performance and reliability, it provides optimal frictional properties, excellent thermal stability, and long-lasting protection for modern CVT systems.

Performance Benefits

- **Superior Anti-Judder Performance:** Enhances driving comfort and reliability by reducing vibration and ensuring smooth operation.
- **Thermal and Oxidation Stability:** Maintains consistent performance under high-temperature conditions, preventing sludge and varnish formation.
- **Excellent Wear Protection:** Protects against wear, rust, and corrosion, extending the life of CVT components.
- **High Power-Transmission Efficiency:** Ensures reliable torque transfer and smooth shifting for a comfortable driving experience.
- **Outstanding Low-Temperature Fluidity:** Improves transmission efficiency and startability in cold conditions.
- **Seal Compatibility and Foam Resistance:** Prevents leakage and ensures stable performance under demanding conditions.

Application

DEXÖ CVT TC is compatible with belt-driven CVTs and recommended for:

- Vehicles requiring TOYOTA CVTF TC or equivalent specifications.
- Cars with SUPER CVT-i systems.

Note: Not suitable for Nissan Extroid CVTs or automatic transmissions (ATs). Always consult the vehicle's owner's manual for proper application.

Meets and Exceeds

- TOYOTA CVTF FE
- HONDA HCF-2
- SUBARU Lineartronic CVTF
- MITSUBISHI DiaQueen CVTF-J4
- SUZUKI CVT Green 2
- DAIHATSU Amix CVTF FE
- MAZDA CVTF 3320

Storage and Handling

- Store in a cool, dry place away from direct sunlight and heat sources.
- Ensure proper disposal according to local regulations.
- Refer to the Safety Data Sheet (SDS) for detailed health and safety information.
- Caution: Before replacing the CVTF, ensure that the CVT system has no underlying issues. Failure to perform prior checks may lead to operational problems.

Typical Properties

Property	Test Method	Value
Appearance	ASTM D4176	B&C
Color	ASTM D1500	Red
Density @ 30°C (g/cm ³)	ASTM D4052	0.8356
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	33.17
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	7.219
Viscosity Index	ASTM D2270	186
Flash Point (°C)	ASTM D92	220
Pour Point (°C)	ASTM D97	-51

