

GLÄT CALCIUM GREASE MP-3

Product Description

Calcium-based, NLGI 3 multipurpose grease for water-resistant lubrication of lightly loaded mechanical parts in wet environments

Product Features & Benefits

Excellent adhesion and water resistance
Corrosion and oxidation inhibition
Prevents leakage in high-vibration or vertical applications
Ideal for outdoor use and moist climates
Economical and widely compatible

Meets or Exceeds

- NLGI Grade: 3
- DIN 51502: G3E-20
- ISO 6743-9: ISO-L-XBAHA3

Typical Properties

Property	Method	Unit
Thickener Type	—	Calcium Soap
Appearance	Visual	Smooth, light brown
NLGI Grade	ASTM D217	3
Worked Penetration (60 strokes)	ASTM D217	220-250
Dropping Point	ASTM D2265	≥90°C
Water Washout Resistance	ASTM D1264	Excellent
Rust Protection (EMCOR)	DIN 51802	0-0
Operating Temp Range	—	-20°C to +60°C

Application

- Chassis greasing points
- Marine trailer wheel bearings
- Agricultural fittings and joints
- Light industrial lubrication points in damp surroundings

Storage & Handling

- Store in a clean, cool, dry location below 40°C
- Keep container sealed to avoid contamination
- Avoid mixing with other greases
- See SDS for full safety, disposal, and handling details

