

VÖNO Mineral Gasoline Engine Oil SAE 30 SF/CF

Product Description

VÖNO 30 SF/CF is a premium-grade, mineral-based, single-grade motor oil designed to meet the lubrication needs of classic cars and motorcycles, especially those without oil filters or equipped with cyclone separators (disk filters). Formulated with mild additive technology, it ensures excellent wear protection, high lubrication reliability, and corrosion resistance under diverse operating conditions. This oil meets the performance requirements of older gasoline and diesel engines, providing robust protection and optimal engine performance.

Performance Benefits

- **Outstanding Corrosion Protection:** Safeguards engine components against rust and corrosion.
- **Excellent Wear Resistance:** Prolongs engine life by reducing friction and wear.
- **High Lubrication Reliability:** Ensures smooth and consistent engine operation.
- **Classic Engine Compatibility:** Suitable for vintage vehicles and motorcycles, including those without advanced filtration systems.
- **Stable Performance:** Maintains viscosity and provides excellent thermal and oxidative stability.

Application

- Classic gasoline and diesel engines (passenger cars and motorcycles).
- Engines without oil filters or equipped with cyclone separators.
- Vintage vehicles requiring unblended or mildly blended lubricants for optimum performance.

Meets and Exceeds

- API SF/CF

Health & Safety, Environment

- Avoid prolonged skin contact; wash with soap and water after handling.
- Dispose of used oil responsibly at authorized collection points.
- Refer to the Safety Data Sheet (SDS) for complete handling and safety guidelines.

Storage and Handling

- Store in a cool, dry location, away from direct sunlight and ignition sources.
- Keep containers tightly sealed to prevent contamination.
- Recommended storage temperature: -10°C to 40°C.

Typical Properties

Property	Test Method	Value
SAE Grade	SAE J300	30
ISO Viscosity Class	DIN 51519	VG 100
Density @ 15°C	DIN 51757	0.8911 g/cm ³
Kinematic Viscosity @ 40°C	ASTM D7042-04	108.9 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042-04	11.66 mm ² /s
Viscosity Index	DIN ISO 2909	94
Pour Point	DIN ISO 3016	-18°C
Flash Point	DIN ISO 2592	252°C
Sulfate Ash	DIN 51575	0.88 %

