

MÖTPRO Semi Synthetic Motorcycle Engine Oil SAE 10W60 SL MA2

Product Description

MÖTPRO 10W60 SL MA2 4T is a premium semi-synthetic motorcycle oil tailored for modern high-performance 4-stroke engines. It combines synthetic and mineral base oils to provide balanced performance, delivering superior wear protection, thermal stability, and consistent lubrication.

Application

- Designed for high-performance sports bikes, dirt bikes, and off-road motorcycles.
- Recommended for motorcycles from manufacturers like KTM, HUSQVARNA, and MOTO GUZZI requiring SAE 10W60 viscosity.
- Suitable for engines with catalytic converters and wet clutches.

Meets and Exceeds

- **API:** SL, SJ
- **JASO:** MA2, MA

Health and Safety

This product is not expected to pose health risks when used as directed. Avoid prolonged skin contact, and wash thoroughly after handling. Refer to the Material Safety Data Sheet (MSDS) for detailed safety instructions.

Typical Properties

Property	Method	Value	Value
Viscosity Grade	SAE J300	-	10W60
Density @ 15°C	ASTM D1298	kg/l	0.8634
Viscosity @ 40°C	ASTM D445	cSt	190.8
Viscosity @ 100°C	ASTM D445	cSt	24.11
Viscosity Index (VI)	ASTM D2270	-	156
Pour Point	ASTM D97	°C	-33
Flash Point	ASTM D92	°C	240
Total Base Number (TBN)	ASTM D2896	mg KOH/g	7.50

Performance Benefits

- **Enhanced Wet Clutch Performance:** Meets JASO MA2 standards for smooth and reliable operation.
- **Improved Shear Stability:** Maintains viscosity under extreme mechanical stress.
- **Extended Engine Protection:** Anti-wear, anti-oxidation, and anti-corrosion properties for long engine life.
- **Thermal Resistance:** Stable performance under high-temperature conditions.
- **Low Volatility:** Reduces oil consumption for economical and efficient use.

Storage and Handling

- Store in a cool, dry place away from direct sunlight.
- Avoid mixing with other lubricants to maintain performance.
- Dispose of used oil in compliance with local regulations.

